



► **OEM Replacement**  
► **Suits Viking® Gear Pumps**

H/VIK replaces the various mechanical component seals suitable for Viking® Motor-speed & Liquid Specific Lines.

► **Materials**

Rotary Face: CAB or SiC  
Stationary Face: SiC or 2205SS  
Elastomers: NBR or Viton  
Metal Parts: 304SS

**PARTS**

**A** Stationary  
**B** Rotary  
**C** Setting Component

**DIMENSIONS**

D1 = Shaft Size  
L1 = Rotary W.L.

D7 = Seat Cavity  
L4 = Seat Height

D3 = Rotary OD  
L = Overall W.L.

| D1      | SEAL             | D7     | L4   | L1   |
|---------|------------------|--------|------|------|
| 0.500"  | Special / Type 1 | -      |      | 28.9 |
| 0.625"  | O-ring / Type 21 | 1.250" | 31.8 | 10.3 |
| 0.750"  | O-ring / Type 2  | 1.375" | 34.9 | 8.5  |
| 1.000"  | O-ring / Type 2  | 1.625" | 41.3 | 11.1 |
| 1.250"  | O-ring / Type 2  | 1.875" | 47.6 | 9.5  |
| 1.4375" | O-ring / Type 21 | 2.250" | 57.1 | 9.5  |